



Shown with Canon CXDI Detector

RadPRO® Mobile 40kW **FLEX PLUS** System

This portable x-ray system incorporates a telescopic column for safe and easy transport and effortless positioning. Its small width makes it ideal for restricted spaces and corridors. Perfect for hospitals, clinics, and universities, it offers mobility and power-saving advantages.

- Counter-balanced telescopic tube column provides effortless positioning, without draining the battery
- Lead crystal batteries retain power longer than acid batteries for less frequent recharging
- Patented wireless distributed antennae system can increase wireless range 40% over single access point systems
- Secondary drive controls on the collimator handles allow positioning without the need to return to the main console
- Collimator features an LED bulb, laser alignment markers for SID accuracy, and selectable copper filtration
- The battery sets charge through a standard power outlet and can be used while charging, avoiding downtime
- Dual battery configuration allows for distributed power to the drive motors, as well as the generator
- Integrates with choice of one or two Canon CXDI 401C/701C/801C wireless flat panel detectors
- Includes enhanced workflow

QUICK SPECS

40 kW x-ray generator (40-150 kVp)

300 kHU x-ray tube

0.7,1.3 mm focal spots

16 degree target angle (important for being able to take images at short SID without adverse heel effect)

Rapid battery charge time

Spectral filtration in collimator

Laser light-field indicator

RadPRO® Mobile 40kW FLEX PLUS

TUBE ARM/STAND

Counterbalanced Tube Arm

Tube arm reach	49.2 in (1,250 mm) Column rotation: ± 315°
Maximal SID to floor	80.7 in (2,050 mm)
Minimal SID to floor	21.6 in (550 mm)

MOBILE UNIT

Weight	1,312 lbs (595 kg)
Size (L x W x H)	53.54 in x 26.4 in x 77.9 in (1,360 mm x 670 mm x 1,980 mm)
Touch screen console	17 in (430 mm) diagonal
Anti-collision system	Frontal
Motorized unit	Up to 4 km/h
Motor Drive (Standard)	Two (2) independent drive motors, one for each wheel (forward and reverse)

GENERATOR SPECS

kW Rating	40 kW
kVp Range	40 to 150 kVp
mA Range	10 - 500 mA Selectable
Number of mA Stations	18
Exposure Time Range	0.001 - 10 sec
mAs Range	0.1 - 500 mAs
Generator Integration	Yes, 3 PT technique
Battery	Capacitor Battery / Capacitor
Anatomical Programs	500+ Anatomical settings
Line Requirements	Single Phase Line Regulation from 100 - 240 Vac (+/-10%)

CANON CXDI DIGITAL DETECTOR

Canon CXDI 401C/701C/801C wireless flat panel detectors (Standard Components: Sensor unit, Battery charger, (2) Batteries, AC/DC cable, X-ray interface unit, IR sensor unit)

VIRTUAL IMAGING

A CANON COMPANY



www.usa.canon.com/dr | 866-288-9729
5600 Broken Sound Blvd., Boca Raton, FL 33487

RadPRO is a registered trademark of Virtual Imaging Inc., a Canon company, in the United States and may also be a registered trademark or trademark in other countries. Canon and CXDI are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product and brand names are trademarks of their respective owners. **Specifications and availability are subject to change without notice.** Not responsible for typographic errors.

©2016 Virtual Imaging, Inc., a Canon company. All rights reserved.

MK-0282 Rev 2

Unit with Telescopic Column

Dimensions in mm.

Tolerance in dimensions ± 1%

